

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims

Claim 1 (Currently amended): A communication portable terminal device, comprising:

a light source, disposed in a housing; and

a light guiding panel, disposed in the housing for guiding a light from the light source,

wherein the light guiding panel includes:

a light transmitting member having an almost plate like shape, wherein the light transmitting member ~~that~~ has:

an incident portion on which the light emitted from the light source is incident, and provided on a back face of the light ~~guiding panel~~ transmitting member, ~~and having an almost plate like shape~~; and

an emitting portion from which the light transmitted from the ~~light~~ source is emitted, and provided on a front face of the light transmitting member; and

~~reflecting units provided on both of the front face and the back face of the light transmitting member for reflecting plural times the light emitted from the light source and incident on the incident portion plural times and guiding the light to the emitting portion,~~ wherein the reflecting units

comprise a first reflecting unit and a second reflecting unit,
wherein the first reflecting unit is provided on the front face
of the light transmitting member and the second reflecting unit
is provided on the back face of the light transmitting member.

Claim 2 (Currently amended): The communication portable terminal device according to claim 1, wherein the second reflecting unit ~~on the back face side~~ includes a reflecting print portion having a peculiar color in a high reflectance on the back face side of the light transmitting member.

Claim 3 (Previously presented): The communication portable terminal device according to claim 1, wherein the incident portion is formed in a curved concave on the back face of the light transmitting member arranged just above the light source.

Claim 4 (Currently amended): The communication portable terminal device according to claim 1, wherein the first reflecting member is provided at approximately a center of the light transmitting member, and a V-shaped groove is provided at a surface boundary ~~on surfaces of a~~ between the first reflecting member disposed on

~~a surface in an almost center of the light transmitting member,~~
and the light transmitting member.

Claim 5 (Currently amended): The communication portable terminal device according to claim 1, wherein the housing ~~that comprises~~ a foldable structure, and includes:

an upper housing having a liquid crystal display unit on an inner side surface thereof; and

a lower housing having an operating key provided on an inner side surface thereof opposed to the inner side surface of the upper housing when the upper housing and the lower housing are set in a closing state, the lower housing being rotatably coupled to the upper housing through a hinge portion; and

wherein the light guiding panel is disposed on an outer side face that is opposite to the inner side surface of the upper housing, and the emitting portion on the front face faces an outside.

Claim 6 (New): The communication portable terminal device according to claim 1, wherein the first reflecting member and the second reflecting member repetitively reflect the light emitted from the light source to propagate the light in the

light transmitting member and to emit the light from the emitting portion.

Claim 7 (New): The communication portable terminal device according to claim 1, wherein the light transmitting member further includes a V-shaped groove, and the V-shaped groove is provided in the vicinity of a surface boundary between the first reflecting member and the light transmitting member.